

可変容量形真空コンデンサ 機種一覧

2011-07-07

形式	ピーク試験電圧 [kVp] (50/60Hz)	RF動作電圧 [kVp]	静電容量 [pF]		最大許容電流 [Arms] (13.56MHz)	回転トルク [N・cm]	回転数 [回転]	外形寸法 [mm]	質量 [kg]	タイプ
			Max	Min						
SCV-300.2G	30	18	20	6	21	19.6	5.5±0.5	L100×ø60.4	0.8	VM
SCV-250.3G	25	15	30	6	27	19.6	5.5±0.5	L100×ø60.4	0.8	VM
SCV-350.3H110	35	21	30	8	38	18	14±0.5	L154×ø110	2.6	VH 110
SCV-150.5	15	9	50	10	27	24.5	12±1.0	L140×ø62.4	0.92	VM
SCV-200.5H82L	20	12	50	8.5	36.1	18	10.5±0.5	L125×ø82	1.6	VH 82L
SCV-150.75GTB	15	9	75	5	40	17.6	6±1.0	L107×ø53	0.8	VT
SCV-250.8H82L	25	15	80	11	72	18	10.5±0.5	L125×ø82	1.6	VH 82L
SCV-250.8G	25	15	80	10	72	19.6	5.5±0.5	L100×ø60.4	0.5	VM
SCV-151H55UW	15	9	100	10	54	18	10.5±0.5	L133.5×ø55	0.7	UW 55
SCV-151H65	15	9	100	10	54	18	14±0.5	L154×ø65	1.2	VH 65
SCV-151GT	15	9	100	20	54	19.6	10±1.0	L130×ø52	0.7	GT
SCV-151	15	9	100	10	54	24.5	12±1.0	L140×ø62.4	0.93	VM
SCV-201H55UW	20	12	100	10	72	18	10.5±0.5	L133.5×ø55	0.7	UW 55
SCV-201H65	20	12	100	10	72	18	14±0.5	L154×ø65	1.2	VH 65
SCV-201H82L	20	12	100	10	72	18	10.5±0.5	L125×ø82	1.6	VH 82L
SCV-351H110	35	21	100	20	126	18	14±0.5	L154×ø110	2.6	VH 110
SCV-201.5H82L	20	12	150	11	108	18	10.5±0.5	L125×ø82	1.6	VH 82L
SCV-201.5H110C	20	12	150	11	108	18	14±0.5	L154×ø110	2.6	VH 110
SCV-251.5H110C	25	15	150	11	135	18	14±0.5	L154×ø110	2.6	VH 110
SCV-201.7G	20	12	170	45	90	19.6	5.5±1.0	L100×ø63	0.8	VM
SCV-152	15	9	200	12	100	24.5	12±1.0	L140×ø62.4	0.95	VM
SCV-152H65C	15	9	200	5.5	120	18	14±0.5	L154×ø65	1.2	VH 65
SCV-152H65	15	9	200	15	108	18	14±0.5	L154×ø65	1.2	VH 65
SCV-202H65	20	12	200	15	120	18	14±0.5	L154×ø65	1.2	VH 65
SCV-202H82L	20	12	200	12	135	18	10.5±0.5	L125×ø82	1.6	VH 82L
SCV-202H82	20	12	200	20	135	18	14±0.5	L154×ø82	1.8	VH 82
SCV-302H110	30	18	200	25	170	18	14±0.5	L154×ø110	2.6	VH 110
SCV-202.2H82L	20	12	220	12	135	18	10.5±0.5	L125×ø82	1.6	VH 82L
SCV-152.5GT	15	9	250	25	80	19.6	10±1.0	L130×ø52.4	0.7	VT
SCV-152.5H55UW	15	9	250	25	94	18	10.5±0.5	L133.5×ø55	0.7	UW 55
SCV-152.5	15	9	250	30	100	24.5	12±1.0	L140×ø62.4	0.93	VM
SCV-152.5H65	15	9	250	15	120	18	14±0.5	L154×ø65	1.2	VH 65
SCV-202.5H65	20	12	250	15	120	18	14±0.5	L154×ø65	1.2	VH 65
SCV-202.5H94	20	12	250	30	150	18	14±0.5	L154×ø94	2.1	VH 94
SCV-202.5H110C	20	12	250	13	170	18	14±0.5	L154×ø110	2.6	VH 110
SCV-252.5H110C	25	15	250	13	170	18	14±0.5	L154×ø110	2.6	VH 110
SCV-53GTB	5	3	330	10	60	17.6	6±1.0	L107×ø53	0.8	VT
SCV-103.3H82LW	10	6	330	15	126	18	10.5±0.5	L125×ø82	1.6	VH 82L
SCV-253.5H110	25	15	350	35	170	18	14±0.5	L154×ø110	2.6	VH 110
SCV-84H82LW	8	4.8	400	15	135	18	10.5±0.5	L125×ø82	1.6	VH 82L
SCV-104G	10	6	450	60	90	19.6	5.5±0.5	L100×ø63	0.8	VM
SCV-204	20	12	450	80	100	24.5	12±1.0	L140×ø89	1.8	VM
SCV-55	5	3	500	30	100	24.5	12±1.0	L140×ø62.4	0.94	VM
SCV-7.55	7.5	4.5	500	30	100	24.5	12±1.0	L140×ø62.4	0.94	VM
SCV-7.55H65	7.5	4.5	500	15	120	18	14±0.5	L154×ø65	1.2	VH 65
SCV-85H55UW	8	4.8	500	50	94	18	10.5±0.5	L133.5×ø55	0.7	UW 55
SCV-105H65G	10	6	500	20	100	18	14±0.5	L154×ø65	1.2	VH 65
SCV-125H65UW	12	7.2	500	50	94	18	10.5±0.5	L133.5×ø65	0.93	UW 55
SCV-155GT	15	9	500	70	80	19.6	10±1.0	L130×ø52.4	0.7	VT
SCV-155G	15	9	500	25	90	24.5	12±1.0	L140×ø62.4	0.94	VM
SCV-155M	15	9	500	50	100	24.5	12±1.0	L140×ø73	1.3	VM
SCV-155H82W	15	9	500	20	135	18	14±0.5	L154×ø82	1.8	VH 82
SCV-155H94	15	9	500	30	150	18	14±0.5	L154×ø94	2.1	VH 94
SCV-155H110	15	9	500	40	170	18	14±0.5	L154×ø110	2.6	VH 110
SCV-205G	20	12	500	50	90	24.5	12±1.0	L140×ø73	1.3	VM

SCV-205H110	20	12	500	40	170	18	14±0.5	L154×ø110	2.6	VH 110
SCV-255H110	25	15	500	40	170	18	14±0.5	L154×ø110	2.6	VH 110
SCV-510GT	5	3	1000	70	80	19.6	10±1.0	L130×ø52.4	0.8	VT
SCV-510H65UW	5	3	1000	100	94	18	10.5±0.5	L133.5×ø65	0.93	UW 55
SCV-510H65G	5	3	1000	20	100	18	14±0.5	L154×ø65	1.3	VH 65
SCV-510M	5	3	1000	50	100	24.5	12±1.0	L140×ø73	1.35	VM
SCV-510H82	5	3	1000	25	135	18	14±0.5	L154×ø82	1.8	VH 82
SCV-510H94	5	3	1000	30	150	18	14±0.5	L154×ø94	2.1	VH 94
SCV-810H65UW	8	4.8	1000	100	94	18	10.5±0.5	L133.5×ø65	0.93	UW 65
SCV-1010G	10	6	1000	50	90	24.5	12±1.0	L140×ø73	1.35	VM
SCV-1010	10	6	1000	80	100	24.5	12±1.0	L140×ø89	1.8	VM
SCV-1010H82W	10	6	1000	25	135	18	14±0.5	L154×ø82	1.8	VH 82
SCV-1010H110	10	6	1000	40	170	18	14±0.5	L154×ø110	2.6	VH 110
SCV-1510H110W	15	9	1000	40	170	18	14±0.5	L154×ø110	2.6	VH 110
SCV-514M	5	3	1400	90	100	24.5	12±1.0	L140×ø73	1.4	VM
SCV-1014G	10	6	1400	90	90	24.5	12±1.0	L140×ø73	1.4	VM
SCV-315H65G	3	1.8	1500	20	100	18	14±0.5	L154×ø65	1.3	VH 65
SCV-415H65UW	4	2.4	1500	150	94	18	10.5±0.5	L133.5×ø65	0.93	UW 65
SCV-515GT	5	3	1500	70	80	19.6	10±1.0	L130×ø60	0.9	VT
SCV-515H82W	5	3	1500	25	135	18	14±0.5	L154×ø82	1.8	VH 82
SCV-515H94	5	3	1500	30	150	18	14±0.5	L154×ø94	2.1	VH 94
SCV-1015H110W	10	6	1500	40	170	18	14±0.5	L154×ø110	2.6	
SCV-320H70UW	3	1.8	2000	200	94	18	10±0.5	L133.5×ø70	1.0	UW 70
SCV-520M	5	3	2000	85	100	24.5	12±1.0	L140×ø89	1.9	VM
SCV-520H110	5	3	2000	40	170	18	14±0.5	L154×ø110	2.6	VH 110
SCV-820H110W	8	4.8	2000	40	170	18	14±0.5	L154×ø110	2.6	VH 110

※at 50W : 50W冷却時 / 50W Cooling